StraPack

StraPack EcoTech

Fully Automated, Wide Belt-Driven Strapping Machine
Extensive Adaptability to Fully Automated Packing Line

■ 80mm wide center belt allows smaller packages to be conveyed.
■ Hinged tabletop provides quick and easy access to the sealing head for easy maintenance and quick adjustments.
■ Jack bolts allow for precise table height adjustments and easy integration to new or existing lines.
■ Inverter system allows for safe and smooth synchronization of conveyor speeds up to 30m (98ft)/min.
■ Various input/output signals (Automatic Operation Start/ Stop/Conveyor Synchronized/Feed-In Ready/Feed-Out Ready/Strap Cycle Completion/Strap End/Error/Emergency Stop) are equipped as standard features, which allows for easy integration into automatic lines.





※ The machine in the picture is shown without jackbolts.



RQ-8FBZ

Standard Specifications (Arch size 650 mm wide x 500 mm high)

Dimension	**Width**	1424 mm
	Height	1346 mm
	Depth	611 mm
	Weight	220 kg
Conveyor Height		750 mm (745 - 800 mm)
Package Size	**Max**	W 550 X H 430 mm
	Min	W 170 X H 50 X L 100 mm
Joint / Strap		heat seal / polypropylene
Strap		5, 6, 9, 12, 15.5 mm
Strap Tension		784 N (80 kgf) / 450 N (46 kgf) *CE spec.
Power Supply		220, 380, 400, 415V Three phase 50/60Hz 1.30kVA

Dimensions and specifications are subject to change without notice.
Modification rights reserved.

© 2021 Strapack Corporation

DISTRIBUTED BY:

CE

ISO 9001 and 14001 Certified

STRAPACK CORPORATION
8-16-6 Ginza, Chuo-ku, Tokyo, 104-0061, JAPAN
(URL) http://www.strapack.com (E-mail) info@strapack.com
STRAPACK INC.
33508 Central Avenue, Union City, CA 94587-2097 U.S.A.
Phone: 1-510-475-6000 Fax: 1-510-475-6090
STRAPACK, N.V./S.A.
Uilenbaan 200, B-2160 Wommelgem, BELGIUM
Phone: 32-3-355-1520 Fax: 32-3-355-1521