StraPack

StraPack EcoTech

Automatic Strapping Machine

- **Strapping Speed**
  Standard strapping rate is 31 straps/min.
- **Jam Resistant**
  The iQ-4000 automatically re-feeds the strap when a misfeed occurs. The strap will not jam if the machine is cycled with no package under the arch.
- **Strapping sizes:**
  The iQ-4000 can be easily adjusted for strap widths of 9mm and 12mm.



iQ-4000

Weight	100 kg
Joint / Strap	heat seal / polypropylene
Strap	(5, 6)**, 9, 12, 15.5 mm
Strap Tension	392 N (40 kgf)
Power Supply	110, 120, 220, 230, 240V Single phase

**Narrow width parts are not available this time
Dimensions and specifications are subject to change without notice.

Modification rights reserved.

© 2024 Strapack Corporation

DISTRIBUTED BY:

ISO 9001 and 14001 Certified

STRAPACK CORPORATION
8-16-6 Ginza, Chuo-ku, Tokyo, 104-0061, JAPAN
Phone 81-3-6278-1806 Fax. 81-3-6278-1807
(URL) hiip://www.strapack.com (E-mail) info@strapack.com
STRAPACK, N.V./S.A.
Uilenbaan 200, B-2160 Wommelgem, BELGIUM
Phone 32-(0)3-355-1520 Fax. 32-(0)3-355-1521