StrapPack®

Semi Automatic, Side-Seal Model



The D-53M2 is the perfect machine for low volume applications in the seafood, poultry, meat, and other food processing industries.

■ The body of the D-53M2 is primarily constructed from stainless steel. The internal components are made of stainless steel or steel with a rust resistant coating.

■ The table height is adjustable to two different positions (732 millimeters or 28 7/8 inches or 642 millimeters or 25 1/4 inches from the floor).

■ A torque tension system provides precise and stable tension.

■ Standard Specifications

Dimension	**Width**	1078 mm	42 -1/2 in.
	Height	1493 mm	58 - 3/4 in.
	Depth	621 mm	24 - 3/8 in.
	Weight	75 kg.	166 lbs.
Package SIze	**Min.**	W 30 X H 100 mm	W 1-1/4 X H 4 in.
	Max. Weight	30 kg	66 lbs.
Joint / Strap/ Coil		heat seal / polypropylene ID 200 X OD 450 X W 200 mm	heat seal / polypropylene ID 8 X OD 18 X W 8 in.
Strap Width		5, 6, 9, 12, 15.5 mm	1/4, 3/8, 1/2, 5/8 in.
Strap Tension		Max. 392N (40 kgf)	Max. 88 lbs.
Power Supply		100-120, 200-240 V 1 Phase 50 / 60 Hz 0.4 KVA	

D-53M2

STRAPACK CORPORATION
8-16-6, Ginza, Chuo-ku, Tokyo, 104-0061, JAPAN
Phone: 81-3-6278-1806 Fax: 81-3-6278-1807
(URL) http://www.strapack.com (E-mail) info@strapack.com
STRAPACK INC.
33508 Central Avenue, Union City, CA 94583-2097 U.S.A.
Phone :1-510-475-6000 Fax:1-510-475-6090
STRAPACK, N.V./S.A.
Uilenbaan 200, B-2160 Wommelgem, BELGIUM
Phone: 32-3-355-1520 Fax: 32-3-355-1521